

ORGANICA

OG Series

Kinwick Materials Limited

Contact: Mr. Wilson Fung 92303714

Email: wilsonfung168@hotmail.com





viewgres >>>

Viewgres is a Sino-German company focusing on Design, R&D, Manufacture and Global trade of ceramic tiles.

Since its establishment in 2006, adhering to the business principle of "Quality and Innovation" and manufacture principle of compliance with renowned German technique and quality, the company has been providing its European and American customers with the first Viewgres gres porcelain, in the world since 2010, and has gained great recognition from European and American market, allowing the company to enjoy outstanding international reputation in the Tile industry.

Viewgres manufactures gres porcelain, of top quality only with variable thickness and superior external and internal quality. In 2015, 1cm Viewgres gres porcelain, is launched into the market by the Viewgres to promote the new concept of Indoor and Outdoor application of quartz tile, allowing global customers to enjoy quality life.

Combination of Chinese and German Perfection

Viewgres gres porcelain, With water absorption rate lower than 0.1% and PEI4-5 wear resistance, the Viewgres gres porcelain features same external and internal texture, soft and natural grain, creating a natural yet fashionable space for customers.

Due To Printing The Relationship May Be Different From The Actual Product Color, Please Prevail In Kind.
由于印刷关系, 可能与实际产品颜色有所差异, 请以实物为准!



Ivory OG1291 22.5x90cm



Beige OG1293 22.5x90cm



Grey OG1295 22.5x90cm



Black OG1299 22.5x90cm



INDOOR & OUTDOOR

1cm & 2cm

ORGANICA has the features of nature and environmental protection and become a low-carbon consumption mode by replacing the expensive wood floor. ORGANICA provides a natural, original ecological and green lifestyle for you who live in the bustling but blundering city.



INDOOR
1CM

Model: OG1291
Size: 22.5X90cm



OUTDOOR
2CM

Model: OG2291A
Size: 22.5X90cm

INDOOR & OUTDOOR

1cm & 2cm

The ORGANICA series with the brand-new design concept has the rough and natural mottled effect of the log with mild color and luster, making you feel the natural smell brought by the wood grain in the warm, natural and simple space.



INDOOR & OUTDOOR

1cm & 2cm



INDOOR
1CM

Model:OG1293
Size:22.5X90cm

Kinwick Materials Limited - Wilson Fung 92303714 Email: wilsonfung168@hotmail.com

The simplicity is the main style in the new era. The space line simply built for ORGANICA expresses the posture of the nature and the elegant color makes it show itself to make people taste the meaning of life.



OUTDOOR
2CM

Model:OG2293A
Size:22.5X90cm

INDOOR & OUTDOOR


1cm & 2cm

ORGANICA has two kinds of innovative thickness design, including 1CM and 2CM and can be used indoor and outdoor. It extends the natural smell into the room to present a pure life impression.



OUTDOOR
2CM

Model: OG2295A
Size: 22.5X90cm



INDOOR & OUTDOOR

1cm & 2cm



The black gray series of ORGANICA has mellow color and luster, with the specification of 225mmX900mm. The product designer reserves the original natural texture, strengthens the line appearance, thus it can be applied with random combination.

Its application in spacious room can reflect the forest in the nature.



INDOOR
1CM
Model: OG1299
Size: 22.5X90cm


The grain of ORGANICA is unique, with primitive and simple temperament. The grain changes a lots, with various colors and natural transition. The original odor of the ancient wood of hundreds of years is perfectly reserved, thus it is a high-end product for decoration.



OUTDOOR
2CM
Model:OG2293A
Size:22.5X90cm



INDOOR
1CM
Model:OG1291
Size:22.5X90cm



INDOOR & OUTDOOR
1cm & 2cm

INDOOR & OUTDOOR

1cm & 2cm



OUTDOOR
2CM Model:OG2293A
Size:22.5X90cm

The application of the special mold makes ORGANICA have the simple touch of the log. It is integrated into the ancient, fresh and comfortable space with the book fragrance and soft morning air in the modern study.



INDOOR
1CM Model:OG1293
Size:22.5X90cm

INDOOR & OUTDOOR

1cm & 2cm



The texture of ORGANICA reaches the level of the original ecological wood grain and is close to the nature. The natural, original ecological and green lifestyle satisfies your solid wood complex in your heart by touching the log texture.

INDOOR
1CM

Model:OG1299
Size:22.5X90cm

INDOOR
1CM

Model:OG3M9
Size:17.1X19.6cm

INDOOR & OUTDOOR

1cm & 2cm



The geometric pasting mode of ORGANICA increases the vertical feeling of the room. The classical and massive black gray, tight and hard texture, fine and salutatory annual ring texture present the versatile space feeling.



INDOOR
1CM

Model:OG1299
Size:22.5X90cm

OUTDOOR
2CM

Model:OG2299A
Size:22.5X90cm



OUTDOOR
2CM


Model:OG2295A
Size:22.5X90cm

Getting the inspiration from the nature, ORGANICA engraves the grain of the versatile ancient wood into the tile design.
After being polished through ink jet and matte, the tile surface is clear and changing, the grain is tilted and crossed and the structure is fine and even, bringing rough and implicit beauty to people.



INDOOR & OUTDOOR

1cm & 2cm



INDOOR
1CM

Model:OG1295
Size:22.5X90cm



**OUTDOOR
2CM**

Model:OG2293A

Size:22.5X90cm

ORGANICA has the features of nature and environmental protection and become a low-carbon consumption mode by replacing the expensive wood floor. ORGANICA provides a natural, original ecological and green lifestyle for you who live in the bustling but blundering city.




**INDOOR
1CM**

Model:OG1293

Size:22.5X90cm

INDOOR & OUTDOOR

1cm & 2cm



Accessories

1CM



2CM



Water jet cutting drilling technology applying on 2cm fullbody porcelain tiles, it will effectively solve the difficult problem due to dredge waterways.

PACKING DETAILS

SERIES	Series	Pcs./Ctn	M ² /Ctn	M ² /Pkt	Ctns./Pkt	Kg./Pkt
ORGANICA	60x60 24"x24" 10mm	4	1.44	46.08	32	1024
	45x90 18"x36" 10mm	3	1.22	37.67	31	1000
	60x60 24"x24" 20mm	2	0.72	23.04	32	1039
	45x90 18"x36" 20mm	1	0.41	24.60	60	1200

Kinwick Materials Limited - Wilson Fung 92303714 Email: wilsonfung168@hotmail.com

TECHNICAL SPECIFICATION

60x60mm 24"x24" 10mm 45x90mm 18"x36" 10mm 60x60mm 24"x24" 20mm 45x90mm 18"x36" 20mm

Complies with standards EN 14411 series B group IIIa Complies with standards ISO 10545 series B group IIIa

	Technical feature	Test Method	Requirements for nominal size 60			ORGANICA	
			Porcelain Tiles	Max Tiles	EN 14411	ISO 10545	ISO 10545
	Length and width	ISO 10545-2	±0.5	±0.5	±0.5	±0.5%	±0.5%
	Thickness		±0.5	±0.5	±0.5	±0.5%	±0.5%
	Straightness of sides		±0.75	±0.5	±0.5	±0.5%	±0.5%
	Rectangularity		±0.75	±0.5	±0.5	±0.5%	±0.5%
	Surface flatness	ISO 10545-2	±0.5	±0.5	±0.5	±0.5%	±0.5%
			±0.5	±0.5	±0.5	±0.5%	±0.5%
			±0.5	±0.5	±0.5	±0.5%	±0.5%
			±0.5	±0.5	±0.5	±0.5%	±0.5%
	Water absorption	ISO 10545-3	≤0.5% individual maximum 0.4%			≤0.5%	≤0.5%
	Breaking strength		≥1300N			≥1300N	≥1300N
	Modulus of rupture		≥38N/mm ²			≥38N/mm ²	≥38N/mm ²
	Abrasion resistance		≤175mm ³			Class 4	Class 4
	Coefficient of thermal linear expansion	ISO 10545-8	Declared value			2.9 X 10 ⁻⁶ /°C	2.9 X 10 ⁻⁶ /°C
	Thermal shock resistance		Pass according to ISO 10545-1			Pass	Pass
	Resistance to household chemicals and serving pots table		Minimum Class B			Passed	Passed
	Resistance to low concentrations of acids and alkalis		Value			—	—
	Resistance to high concentrations of acids and alkalis	ISO 10545-10	Value			—	—
	Molecular expansion (mm/m)		Declared value			≤0.72 mm/m	≤0.72 mm/m
	Frost resistance		Pass according to ISO 10545-1			Pass	Pass
	Impact resistance, as coefficient of restitution		Declared value			≥0.67	≥0.7
	Moisture vapour	EN 161	≤0.03			7	7
	Bond strength/adhesion		Declared value			N/A	N/A
	Reaction to fire		Class A1 or A1			A1	A1
	Resistance to staining		Minimum Class 3			Class 5	Class 5
	Coefficient of friction(COF)	3 C.F.A. (Reg. CECB)	DIN 51099 (at 1450N)			1.30Dry 1.10Wet	1.31Dry 1.10Wet
	Dynamic coefficient of friction		AS/NZS 4581:2012			0.74Dry 0.62Wet	0.74Dry 0.62Wet
	Static coefficient of friction(COFS)		ASTM C1028-2007			0.60Dry 0.50Wet	0.60Dry 0.50Wet
	Slip resistance Classification of Foot Pedestrian Surface Materials		AS 4586:2013 Appendix A			P4-P5	P5
	Penetration Friction Test	Appendix A of EN 515	Approved for compliance with EN 1525			Class 5	Class 5
	Resilient Floor Test		Declared value			C	C
	Rock Ramp Test		Declared value			R9-R10	R11
	Penetration Friction Test		Declared value			PTV >40Dry PTV >30Wet	PTV >40Dry PTV >30Wet

www.viewgres.com

Kinwick Materials Limited - Wilson Fung 92303714 Email: wilsonfung168@hotmail.com